

Stroke limiter with position indicator



Reference	To be used with:	DN
-	**VM / NO - DA	80 ÷ 100
ZIN005	-	-
ZLI001	DK / NC	15 ÷ 32
ZLI002	DK / NO - DA	15 ÷ 32
ZLI003	DKM / NC	40
ZLI004	DKM / NC	50 ÷ 65
ZLI005	DKM / NO - DA	40 ÷ 65
ZLI006	DKP / NC	25 ÷ 40
ZLI007	DKP / NC	50 ÷ 65
ZLI008	DKP / NO - DA	25 ÷ 40
ZLI009	DKP / NO - DA	50 ÷ 65
ZLI010	CM / CP	12 ÷ 15



Stroke limiter with position indicator

- Upper part (PVC-U)
 - Bottom part (PVC-U)
 - Bolts (zinc plated steel)
 - Nuts (zinc plated steel)
 - Gasket (NBR)
 - Reinforcing ring (Stainless steel)
- The reinforcing bush are used to reinforce the pipe PE100 (SDR11) e PE-X, to elong the lifetime of the pipeline and to reduce the collapse risk of the pipe in disadvantages conditions. They use is particularly suggested using PE-X pipes. The two tightening keys (d.16-63 and d.75-110) are important tools to install the **MAGNUM 3G** fittings