

# S12NV - 24V AC -true union 2-way solenoid valve

2 way solenoid valve with NPT threaded female union ends.

Function: Normally closed. Power supply: 24V AC



## EPDM

Reference	d	DN	A	B	C	H	H <sub>1</sub>	L	Z	E	M	g
S12NV0414E024A	1/4"	4	24	100	103	91	46	15	61	42	52	400
S12NV0438E024A	3/8"	4	24	100	103	92	46	16	60	42	52	400
S12NV0614E024A	1/4"	6	24	100	103	91	45	15	61	42	52	400
S12NV0638E024A	3/8"	6	24	100	103	92	46	16	60	42	52	400
S12NV0814E024A	1/4"	8	24	100	103	91	45	15	61	42	52	400
S12NV0838E024A	3/8"	8	24	100	103	92	46	16	60	42	52	400

## S12NV - 24V AC -true union 2-way solenoid valve

Reference	d	DN	A	B	C	H	H <sub>1</sub>	L	Z	E	M	g
S12NV0414F024A	1/4"	4	24	100	103	91	45	15	61	42	52	400
S12NV0438F024A	3/8"	4	24	100	103	92	46	16	60	42	52	400
S12NV0614F024A	1/4"	6	24	100	103	91	45	15	61	42	52	400
S12NV0638F024A	3/8"	6	24	100	103	92	46	16	60	42	52	400
S12NV0814F024A	1/4"	8	24	100	103	91	45	15	61	42	52	400
S12NV0838F024A	3/8"	8	24	100	103	92	46	16	60	42	52	400

# S12NV - 24V AC -true union 2-way solenoid valve

- Installation flexibility and ease of maintenance: high-performance solenoid electric actuator with internal moving parts designed to exceed 5 million maintenance free operating cycles. Adjustable circular section coil with IP65 protection class.
  - DIN 43650 electrical connector supplied as standard: includes LED indicator light and rectifier (in the case of an AC coil).
  - Lever shutter in EPDM or FKM and lever in stainless steel.
  - Suitable for use with aggressive fluids: no metal component in contact with the fluid or the external environment; all the screws are covered by PE protection plugs.
  - Emergency override
- 
- 2-Way PVC-U body
  - Installation flexibility and ease of maintenance: high-performance solenoid electric actuator designed to exceed 5 million maintenance-free operating cycles
  - Adjustable circular section coil with IP65 protection class.
  - Integrated override with the possibility of being installed in 3 different positions.
  - Lever shutter in EPDM or FKM and lever in stainless steel.
  - DIN 43650 electrical connector supplied as standard: includes LED indicator light and rectifier (in the case of an AC coil).