

S22IV - 110V AC - true union 2-way solenoid valve

2 way solenoid valve with female union ends for solvent welding.

Function: Normally closed. Power supply: 110V AC



EPDM

| Reference | d | DN | A | B | C | H | H ₁ | L | Z | E | M | g |
|----------------|----|----|----|-----|-----|-----|----------------|----|----|----|----|------|
| S22IV0816E110A | 16 | 8 | 34 | 115 | 130 | 99 | 50 | 14 | 71 | 54 | 67 | 1000 |
| S22IV0820E110A | 20 | 8 | 34 | 115 | 130 | 103 | 52 | 16 | 71 | 54 | 67 | 1000 |
| S22IV1016E110A | 16 | 10 | 34 | 115 | 130 | 99 | 50 | 14 | 71 | 54 | 67 | 1000 |
| S22IV1020E110A | 20 | 10 | 34 | 115 | 130 | 103 | 52 | 16 | 71 | 54 | 67 | 1000 |
| S22IV1516E110A | 16 | 15 | 34 | 115 | 130 | 99 | 50 | 14 | 71 | 54 | 67 | 1000 |
| S22IV1520E110A | 20 | 15 | 34 | 115 | 130 | 103 | 52 | 16 | 71 | 54 | 67 | 1000 |

S22IV - 110V AC - true union 2-way solenoid valve

| Reference | d | DN | A | B | C | H | H ₁ | L | Z | E | M | g |
|----------------|----|----|----|-----|-----|-----|----------------|----|----|----|----|------|
| S22IV0816F110A | 16 | 8 | 34 | 115 | 130 | 99 | 50 | 14 | 71 | 54 | 67 | 1000 |
| S22IV0820F110A | 20 | 8 | 34 | 115 | 130 | 103 | 52 | 16 | 71 | 54 | 67 | 1000 |
| S22IV1016F110A | 16 | 10 | 34 | 115 | 130 | 99 | 50 | 14 | 71 | 54 | 67 | 1000 |
| S22IV1020F110A | 20 | 10 | 34 | 115 | 130 | 103 | 52 | 16 | 71 | 54 | 67 | 1000 |
| S22IV1516F110A | 16 | 15 | 34 | 115 | 130 | 99 | 50 | 14 | 71 | 54 | 67 | 1000 |
| S22IV1520F110A | 20 | 15 | 34 | 115 | 130 | 103 | 52 | 16 | 71 | 54 | 67 | 1000 |



S22IV - 110V AC - true union 2-way solenoid valve

- Installation flexibility and ease of maintenance: high-performance solenoid electric actuator with internal moving parts designed to exceed 5 million maintenance free operating cycles. Adjustable circular section coil with IP65 protection class.
 - DIN 43650 electrical connector supplied as standard: includes LED indicator light and rectifier (in the case of an AC coil).
 - Lever shutter in EPDM or FKM and lever in stainless steel.
 - Suitable for use with aggressive fluids: no metal component in contact with the fluid or the external environment; all the screws are covered by PE protection plugs.
 - Emergency override
-
- 2-Way PVC-U body
 - Installation flexibility and ease of maintenance: high-performance solenoid electric actuator designed to exceed 5 million maintenance-free operating cycles
 - Adjustable circular section coil with IP65 protection class.
 - Integrated override with the possibility of being installed in 3 different positions.
 - Lever shutter in EPDM or FKM and lever in stainless steel.
 - DIN 43650 electrical connector supplied as standard: includes LED indicator light and rectifier (in the case of an AC coil).