Oaliaxis

Formwork with handle PVC

Light duty traffic areas such as garage fronts, private driveways, parkings, pedestrian areas: to use as an alternative to the normal cover for catch basin when the surface appearance has to be kept unaltered.

Material: PVC.


The cover's cavity has to be filled with the proper material (as shown in the pictures).


Once installed, it can be easily lifted off by the handle.

Durability: PVC specifications and structure design give this product a great resistance against atmospheric agents and ageing, and ensure dimensional stability in time.

Benefits:

- handle tested to resist (certified traction resistance of 220 kg)
- handle easily extractable (handle fixed with screws on the bottom of the formwork)
- manageable and practical
- handle fixed with screws on the bottom of the formwork so that it can be easily dismantled for cleaning
- iron mesh can be placed inside to improve load resistance
- designed to support heavy loads
- thicker section to avoid lateral bendings
- resistant to acids and atmospheric agents
- certified load resistance (more than 203 kn = 20,3t). Test have been carried out by Istituto Giordano.





Reference	RAL	A (mm)	B [mm]	H (mm)	H1 (mm)	Kg	Dim (mm)	Dim. Concrete catch basin (mm)	Material
ECM3504	7035	350x350	370x370	70	50	2,5	350x350	300X300	PVC
ECM3804	7035	350x350	370X370	105	85	2,6	350x350	300X300	PVC
ECM4504	7035	450x450	470x470	70	50	3,5	450x450	400X400	PVC
ECM5004	7035	550x550	570x570	70	50	4,8	550x550	500X500	PVC

