

# Bend 45° S/S

Push-Fit PVC-U Fittings EN 1401  
Gaskets EN 681-1 DIN 4060

RAL 8023 Red - RAL 7037 Grey



Reference	DN (mm)	S (mm)	Z1 (mm)	Z2 (mm)	L1 (mm)	L2 (mm)	$\alpha$	RAL	Type	Gasket	Version
0121142	110	3,2	27	36	58	50	45°	7037	SN8-SDR34	Bloccata/Fixed	-
012115E	110	3,2	27	36	58	50	45°	8023	-	Standard	-
0701242	125	3,2	29	40	68	56	45°	7037	-	Bloccata/Fixed	-
070125E	125	3,2	29	40	68	56	45°	8023	-	Standard	-
0702242	125	3,7	29	49	68	56	45	7035	SN8-SDR34	Standard	-
0701642	160	4,0	37	51	80	66	45°	7037	-	Bloccata/Fixed	-
010165E	160	4,0	14	28	82	72	15°	8023	-	Standard	-
0701542	160	4,7	37	51	80	66	45	8023	SN8-SDR34	Standard	-
0702042	200	4,9	46	64	100	84	45°	7037	-	Bloccata/Fixed	-
070205E	200	4,9	46	64	100	84	45°	8023	-	Standard	-
0122552	250	6,2	58	79	125	96	45°	7037	-	Standard	-
0122591	250	6,2	58	79	125	96	45°	8023	-	Standard	-
0123052	315	7,7	73	100	144	118	45°	7037	-	Standard	-
0123091	315	7,7	73	100	144	118	45°	8023	-	Standard	-
1124052	400	9,8	91	126	165	140	45°	7037	-	Standard	-
1124091	400	9,8	91	126	165	140	45°	8023	-	Standard	-
1125052	500	9,8	103	152	160	150	45°	7037	-	Standard	-
1125091	500	9,8	103	152	160	150	45°	8023	-	Standard	-
N126391	630	-	-	-	-	-	45°	8023	Fabricated	Standard	upon request