

# Bend 30° S/S

Push-Fit PVC-U Fittings EN 1401  
Gaskets EN 681-1 DIN 4060

RAL 8023 Red - RAL 7037 Grey



Reference	DN (mm)	S (mm)	Z1 (mm)	Z2 (mm)	L1 (mm)	L2 (mm)	$\alpha$	RAL	Type	Gasket	Version
011115E	110	3,2	17	29	61	50	30°	8023	SN8-SDR34	Standard	-
0111142	110	3,2	17	29	61	50	30°	7037	SN8-SDR34	Bloccata/Fixed	-
0111242	125	3,2	19	29	68	62	30°	7037	-	Bloccata/Fixed	-
011125E	125	3,2	19	29	68	62	30°	8023	-	Standard	-
0111642	160	4,0	25	40	82	72	30°	7037	-	Bloccata/Fixed	-
011165E	160	4,0	25	40	82	72	30°	8023	-	Standard	-
0112042	200	4,9	30	49	100	86	30°	7037	-	Bloccata/Fixed	-
011205E	200	4,9	30	49	100	86	30°	8023	-	Standard	-
0112552	250	6,2	37	59	134	103	30°	7037	-	Standard	-
0112591	250	6,2	37	59	134	103	30°	8023	-	Standard	-
0113052	315	7,7	47	74	144	118	30°	7037	-	Standard	-
0113091	315	7,7	47	74	144	118	30°	8023	-	Standard	-
1114052	400	9,8	65	98	165	140	30°	7037	-	Standard	-
1114091	400	9,8	65	98	165	140	30°	8023	-	Standard	-
N115091	500	12,2	165	230	160	250	30°	8023	Fabricated	Standard	upon request
N116391	630	-	-	-	-	-	30°	8023	Fabricated	Standard	upon request