

# Bend 87°30' S/S

Push-Fit PVC-U Fittings EN 1401  
Gaskets EN 681-1 DIN 4060

RAL 8023 Red - RAL 7037 Grey



Reference	DN (mm)	S (mm)	Z1 (mm)	Z2 (mm)	L1 (mm)	L2 (mm)	$\alpha$	RAL	Type	Gasket	Version
0711142	110	3,2	59	69	58	50	87° 30'	7037	SN8-SDR34	Bloccata/Fixed	-
071115E	110	3,2	59	69	58	50	87° 30'	8023	SN8-SDR34	Standard	-
0711242	125	3,2	65	77	67	56	87° 30'	7037	-	Bloccata/Fixed	-
071125E	125	3,2	65	77	67	56	87° 30'	8023	-	Standard	-
0711642	160	4,0	84	96	80	66	87° 30'	7037	-	Bloccata/Fixed	-
071165E	160	4,0	84	96	80	66	87° 30'	8023	-	Standard	-
0712042	200	4,9	105	122	100	85	87° 30'	7037	-	Bloccata/Fixed	-
071205E	200	4,9	105	122	100	85	87° 30'	8023	-	Standard	-
0142552	250	6,2	132	154	136	103	87° 30'	7037	-	Standard	-
0142591	250	6,2	132	154	136	103	87° 30'	8023	-	Standard	-
0143052	315	7,7	166	192	144	114	87° 30'	7037	-	Standard	-
0143091	315	7,7	166	192	144	114	87° 30'	8023	-	Standard	-
1144052	400	9,8	211	244	160	140	87° 30'	7037	-	Standard	-
1144091	400	9,8	211	244	160	140	87° 30'	8023	-	Standard	-
1145052	500	9,8	380	430	160	150	87° 30'	7037	Fabricated	Standard	-
1145091	500	9,8	380	430	160	150	87° 30'	8023	Fabricated	Standard	-
N146391	630	-	-	-	-	-	87° 30'	8023	Fabricated	Standard	upon request