

Branch 87°30' D/S

Push-Fit PVC-U Fittings EN 1401
Gaskets EN 681-1 DIN 4060

RAL 8023 Red - RAL 7037 Grey



Reference	DN (mm)	DN1 (mm)	S (mm)	S1 (mm)	Z1 (mm)	Z2 (mm)	Z3 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	α	RAL	Type	Gasket
0341142	110	110	3,2	3,2	55	69	69	60	50	50	87° 30'	7037	SN8-SDR34	Bloccata
034115E	110	110	3,2	3,2	55	69	69	60	50	50	87° 30'	8023	SN8-SDR34	Standard
0811242	125	125	3,2	3,2	66	70	78	62	62	62	87° 30'	7037	-	Bloccata
081125E	125	125	3,2	3,2	66	70	78	62	62	62	87° 30'	8023	-	Standard
0811642	160	160	4,0	-	76	98	98	88	74	74	87° 30'	7037	-	Bloccata
081165E	160	160	4,0	-	76	98	98	88	74	74	87° 30'	8023	-	Standard
0812042	200	200	4,9	-	105	119	119	100	86	86	87° 30'	7037	-	Bloccata
081205E	200	200	4,9	-	105	119	119	100	86	86	87° 30'	8023	-	Standard
0342552	250	250	6,2	-	120	152	152	135	101	101	87° 30'	7037	-	Standard
0342591	250	250	6,2	-	120	152	152	135	101	101	87° 30'	8023	-	Standard
1343052	315	315	7,7	7,7	166	185	174	146	114	114	87° 30'	7037	-	Standard

Branch 87°30' D/S

Reference	DN (mm)	DN1 (mm)	S (mm)	S1 (mm)	Z1 (mm)	Z2 (mm)	Z3 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	α	RAL	Type	Gasket
1343091	315	315	7,7	7.7	166	185	174	146	114	114	87° 30'	8023	-	Standard
1344051	400	400	9,8	9.8	250	270	230	215	175	175	87° 30'	8023	Thermoformed	Standard
1344052	400	400	9,8	9.8	250	270	230	215	175	175	87° 30'	7037	Thermoformed	Standard
N345091	500	500	12,3	12.3	265	355	345	295	245	245	87° 30'	8023	Fabricated	Standard