


# Reduced branch 87°30' T/S

Push-Fit PVC-U Fittings EN 1401  
Gaskets EN 681-1 DIN 4060

RAL 8023 Red - RAL 7037 Grey



Reference	DN (mm)	DN1 (mm)	S (mm)	S1 (mm)	Z1 (mm)	Z2 (mm)	Z3 (mm)	L1 (mm)	L3 (mm)	$\alpha$	RAL	Gasket	Version	Type
0351741	160	110	4,0	3.2	70	75	95	72	56	87° 30'	8023	Bloccata/ Fixed	-	-
0463642	160	125	4,0	3.2	85	81	94	72	62	87° 30'	7037	Bloccata/ Fixed	-	-
0460141	200	110	4,9	3.2	108	110	120	86	60	87° 30'	8023	Bloccata/ Fixed	-	-
0460242	200	125	4,9	3.2	108	110	120	86	62	87° 30'	7037	Bloccata/ Fixed	-	-
0460642	200	160	4,9	4.0	108	110	132	86	74	87° 30'	7037	Bloccata/ Fixed	-	-
0460641	200	160	4,9	4.0	108	110	132	86	74	87° 30'	8023	Bloccata/ Fixed	-	-
1461242	250	125	6,2	3.2	100	100	132	103	130	87° 30'	7037	Bloccata/ Fixed	-	-
1461642	250	160	6,2	4.0	100	100	134	107	126	87° 30'	7037	Bloccata/ Fixed	-	-
1461651	250	160	6,2	4.0	100	100	134	107	126	87° 30'	8023	Bloccata/ Fixed	upon request	-
1462051	250	200	6,2	4.9	100	143	136	113	120	87° 30'	8023	Bloccata/ Fixed	upon request	-
1464141	315	110	7,7	3.2	150	150	176	116	56	87° 30'	8023	Bloccata/ Fixed	upon request	-

# Reduced branch 87°30' T/S

Reference	DN (mm)	DN1 (mm)	S (mm)	S1 (mm)	Z1 (mm)	Z2 (mm)	Z3 (mm)	L1 (mm)	L3 (mm)	α	RAL	Gasket	Version	Type
1464342	315	125	7,7	3.2	150	150	176	116	65	87° 30'	7037	Bloccata/ Fixed	-	-
1464242	315	160	7,7	4.0	150	150	180	116	73	87° 30'	7037	Bloccata/ Fixed	-	-
1464442	315	200	7,7	4.9	150	150	185	116	87	87° 30'	7037	Bloccata/ Fixed	-	-
1464451	315	200	7,7	4.9	150	150	185	116	87	87° 30'	8023	Bloccata/ Fixed	-	-
1463342	400	125	9,8	3.2	192	192	240	145	65	87° 30'	7037	Bloccata/ Fixed	upon request	Thermoformed
1467741	400	200	9,8	4.9	192	192	250	145	95	87° 30'	8023	Bloccata/ Fixed	-	Thermoformed
1468842	400	250	9,8	6.2	227	227	270	145	105	87° 30'	7037	Bloccata/ Fixed	-	Thermoformed
1469942	400	315	9,8	7.7	227	227	260	145	125	87° 30'	7037	Bloccata/ Fixed	-	Thermoformed