

Saddle 45°

Push-Fit PVC-U Fittings EN 1401
Gaskets EN 681-1 DIN 4060

RAL 8023 Red - RAL 7037 Grey



Reference	DN (mm)	DN1 (mm)	S (mm)	S1 (mm)	Z (mm)	L1 (mm)	L2 (mm)	L3 (mm)	α	RAL	Gasket	Type
0438042	160	125	3,2	3,0	128	62	65	300	45°	7037	Bloccata/Fixed	-
0438091	160	125	3,2	3,0	128	62	65	300	45°	8023	Standard	-
0438242	200	125	4,1	3,0	128	62	65	340	45°	7037	Bloccata/Fixed	-
0438291	200	125	4,1	3,0	128	62	65	340	45°	8023	Standard	-
0438442	200	160	4,1	3,6	165	73	85	390	45°	7037	Bloccata/Fixed	-
0438491	200	160	4,1	3,6	165	73	85	390	45°	8023	Standard	-
0438642	250	125	5,5	3,0	128	62	92	350	45°	7037	Bloccata/Fixed	-
0438691	250	125	5,5	3,0	128	62	92	350	45°	8023	Standard	-
0438842	250	160	5,5	3,6	165	73	92	400	45°	7037	Bloccata/Fixed	-
0438891	250	160	5,5	3,6	165	73	92	400	45°	8023	Standard	-
1439091	315	125	5,5	3,0	128	62	92	350	45°	8023	Standard	-
0439442	315	160	6,9	3,6	165	73	110	432	45°	7037	Bloccata/Fixed	-
0439491	315	160	6,9	3,6	165	73	110	432	45°	8023	Standard	-
1433242	315	200	6,0	4,4	236	95	86	513	45°	7037	Bloccata/Fixed	upon request
1439191	400	125	5,5	3,0	128	62	92	350	45°	8023	Standard	-
1439591	400	160	5,5	3,6	165	73	92	400	45°	8023	Standard	-
1439242	500	125	5,5	3	128	62	92	350	45°	7037	Bloccata/Fixed	upon request
1439291	500	125	5,5	3,0	128	62	92	350	45°	8023	Standard	-
1439691	500	160	5,5	3,6	165	73	92	400	45°	8023	Standard	-