

# FSFV-PVC-T

Float: PP (Polypropylene) red



Reference	R	Flow rate range for NaOH 30% [l/h]	B	E	C
FSFV034T3M0054	3/4"	2,5 - 54	397	350	356
FSFV034T3M0115	3/4"	6 - 115	397	350	356
FSFV034T3M0235	3/4"	11 - 235	397	350	356
FSFV034T3M0410	3/4"	28 - 410	397	350	356
FSFV100T3M0125	1"	6 - 125	401	350	356
FSFV100T3M0200	1"	10 - 200	401	350	356
FSFV100T3M0395	1"	11 - 395	401	350	356
FSFV100T3M0650	1"	25 - 650	401	350	356
FSFV112T3M1000	1"1/2	50 - 1000	413	350	356
FSFV112T3M1500	1"1/2	100 - 1500	413	350	356
FSFV112T3M1600	1"1/2	120 - 1600	413	350	356
FSFV114T3M0600	1"1/4	25 - 600	406	350	356
FSFV114T3M1100	1"1/4	55 - 1100	406	350	356
FSFV114T3M1700	1"1/4	100 - 1700	406	350	356
FSFV200T3M1700	2"	60 - 1700	421	350	356
FSFV200T3M2500	2"	90 - 2500	421	350	356
FSFV200T3M4000	2"	200 - 4000	421	350	356
FSFV212T3M0022	2"1/2	4400 - 22000	444	350	356
FSFV212T3M6000	2"1/2	670 - 6000	444	350	356
FSFV212T3M7500	2"1/2	500 - 7500	444	350	356

## FSFV-PVC-T

- Metering tubes are available in Trogamid (PA) suitable for most inert media, PVC-U suitable for slight corrosive media and Polysulfone (PSU) suitable for corrosive media on an extended operating temperature range.
  - End connectors available in PVC-U, PVC-C, PP, SS, Malleable Cast Iron. Male threads moulded onto the end of the metering tube are used for easy mounting of unions. Standard unions are in PVC-U but others are available according to the different working conditions; Metal unions widen the range of operating conditions such as pressure and temperature.
  - The floats are available in Stainless Steel AISI 316 and in PP to match the proper chemical compatibility with the flow medium and to offer different measuring ranges.
  - Magnetic Float option is available to be combined with micro switches for MIN and MAX alarm, clamped on the guide of the flowmeter. The micro switches, housing a bistable reed contact are activated by the passage of the magnet incorporated into the float.
  - Flowmeters body are equipped with a double guide allowing the installation of two alarm in a very close position.
  - Double scale option available for specific application requirements to customize measuring units for an easy conversion or comprehension of the flow rate values.
- Wide choice of measuring scales: water scale from 1,5 to 50.000 l/h, HCl scale from 1,4 to 23.000 l/h, NaOH 30% scale from 0,25 to 43.000 l/h, NaOH 50% scale from 0,025 to 40.000 l/h, Air scale from 0,025 to 500 Nm<sup>3</sup>/h
  - Wide choice of end connections available in PVC-U, PVC-C, PP-H, AISI 316 SS, Carbon Steel
  - Eight different diameters
  - Three different plastic tube materials: PA, PVC and PSU
  - Float materials available in SS and PP, with or without magnet
  - High level of accuracy: FS accuracy class 2,5; FC accuracy class 4
  - Simple operation and very limited maintenance.
  - Other engineering units like LPM, m<sup>3</sup>/h or % together with double scales and special scales are available on request.