

# FCIV-Polysulfone

Float: PP (Polypropylene) red



Reference	d	Flow rate range for NaOH 30% [l/h]	B	E	C
FCIV016P3M0003	16	0,25 - 3	199	165	171
FCIV016P3M0017	16	1 - 17	199	165	171
FCIV016P3M0045	16	2,5 - 45	199	165	171
FCIV016P3M0075	16	5 - 75	199	165	171
FCIV020P3M0034	20	2 - 34	208	170	176
FCIV020P3M0063	20	2,5 - 63	208	170	176
FCIV020P3M0104	20	5 - 104	208	170	176
FCIV020P3M0125	20	1 - 12,5	208	170	176
FCIV020P3M0170	20	10 - 170	208	170	176
FCIV025P3M0060	25	3,5 - 60	229	185	191
FCIV025P3M0092	25	5 - 92	229	185	191
FCIV025P3M0165	25	8 - 165	229	185	191
FCIV025P3M0380	25	20 - 380	229	185	191
FCIV032P3M0090	32	5 - 90	250	200	206
FCIV032P3M0150	32	7,5 - 150	250	200	206
FCIV032P3M0360	32	20 - 360	250	200	206
FCIV032P3M0650	32	25 - 650	250	200	206

## FCIV-Polysulfone

- Metering tubes are available in Trogamid (PA) suitable for most inert media, PVC-U suitable for slight corrosive media and Polysulfone (PSU) suitable for corrosive media on an extended operating temperature range. End connectors available in PVC-U, PVC-C, PP, SS, Malleable Cast Iron. Male threads moulded onto the end of the metering tube are used for easy mounting of unions. Standard unions are in PVC-U but others are available according to the different working conditions; Metal unions widen the range of operating conditions such as pressure and temperature. The floats are available in Stainless Steel AISI 316 and in PP to match the proper chemical compatibility with the flow medium and to offer different measuring ranges. Magnetic Float option is available to be combined with micro switches for MIN and MAX alarm, clamped on the guide of the flowmeter. The micro switches, housing a bistable reed contact are activated by the passage of the magnet incorporated into the float. Flowmeters body are equipped with a double guide allowing the installation of two alarm in a very close position. Double scale option available for specific application requirements to customize measuring units for an easy conversion or comprehension of the flow rate values.
- Wide choice of measuring scales: water scale from 1,5 to 50.000 l/h, HCl scale from 1,4 to 23.000 l/h, NaOH 30% scale from 0,25 to 43.000 l/h, NaOH 50% scale from 0,025 to 40.000 l/h, Air scale from 0,025 to 500 Nm<sup>3</sup>/h • Wide choice of end connections available in PVC-U, PVC-C, PP-H, AISI 316 SS, Carbon Steel • Eight different diameters • Three different plastic tube materials: PA, PVC and PSU • Float materials available in SS and PP, with or without magnet • High level of accuracy: FS accuracy class 2,5; FC accuracy class 4 • Simple operation and very limited maintenance. • Other engineering units like LPM, m<sup>3</sup>/h or % together with double scales and special scales are available on request.