

C300 - Conductivity Sensor

SS body and electrodes conductivity sensors with temperature sensor (Pt1000) included.



Reference	Description	Flow Rate Range	Cell Constant	Connection	Installation	Weight (gr.)
C300.001.TCCK	Simplified Cell constant	0,055 $\mu\text{S}/\text{cm}$ to 200 $\mu\text{S}/\text{cm}$ (18,2M Ω *cm to 5K Ω *cm)	0,01	3 m	EG12SS	150
C300.001TC	-	0,055 $\mu\text{S}/\text{cm}$ to 200 $\mu\text{S}/\text{cm}$ (18,2M Ω *cm to 5K Ω *cm)	0,01	3 m	EG50P EG75P EG12SS	150
C300.10TC	-	10 $\mu\text{S}/\text{cm}$ to 200000 $\mu\text{S}/\text{cm}$	10	3 m	EG50P EG75P EG12SS	150

C300 – Conductivity Sensor

APPLICATIONS:

- Agriculture and fertilizing system
- Water treatment
- Foods industry
- Aquaculture
- Ultrapure water application: production and use

MAIN FEATURES:

- Stainless steel measuring surfaces
- Considerable ratio performance/price
- Temperature sensor included
- Wide range of cell constant
- Rugged sensor body in PP (C100)
- Sensor in SS completely (C300)
- C300.001TCCK with certified cell constant