

F3.05.XX

Paddlewheel Flow Switch



Reference	Version	Power supply	Lenght	Main Wetted Materials	Enclosure
F3.05.01	Hall	12 - 24 VCC	L0	C-PVC \$ EPDM	IP65
F3.05.02	Hall	12 - 24 VCC	L0	C-PVC \$ FKM	IP65
F3.05.03	Hall	12 - 24 VCC	L1	C-PVC \$ EPDM	IP65
F3.05.04	Hall	12 - 24 VCC	L1	C-PVC \$ FKM	IP65
F3.05.05	Hall	12 - 24 VCC	L0	PVDF \$ EPDM	IP65
F3.05.06	Hall	12 - 24 VCC	L0	PVDF \$ FKM	IP65
F3.05.07	Hall	12 - 24 VCC	L1	PVDF \$ EPDM	IP65
F3.05.08	Hall	12 - 24 VCC	L1	PVDF \$ FKM	IP65
F3.05.09	Hall	12 - 24 VCC	L0	316L SS \$ EPDM	IP65
F3.05.10	Hall	12 - 24 VCC	L0	316L SS \$ FKM	IP65
F3.05.11	Hall	12 - 24 VCC	L1	316L SS \$ EPDM	IP65
F3.05.12	Hall	12 - 24 VCC	L1	316L SS \$ FKM	IP65



F3.05.XX

APPLICATIONS:

- Pump protection
- Filtration systems
- Cooling water systems

MAIN FEATURES:

- C-PVC, PVDF, Stainless Steel body
- Easy insertion system
- High chemical resistance
- No-Flow alarm relay output
- Highly visible Local Bicolour Status Indicator
- Maintenance free
- Very low pressure drop