

M9.00.XX

2-Wires Flow Monitor and Transmitter Field mount



Reference	Power supply	Wire power Technology	Sensor Input	Output	Lenght	Main Wetted Materials
M9.00.01	12 - 24 VCC	2 wire	Flow (Frequency)	1*(4-20mA) \$ 1*(S.S.R.)	L0	C-PVC \$ EPDM
M9.00.02	12 - 24 VCC	2 wire	Flow (Frequency)	1*(4-20mA) \$ 1*(S.S.R.)	L0	C-PVC \$ FKM
M9.00.03	12 - 24 VCC	2 wire	Flow (Frequency)	1*(4-20mA) \$ 1*(S.S.R.)	L1	C-PVC \$ EPDM
M9.00.04	12 - 24 VCC	2 wire	Flow (Frequency)	1*(4-20mA) \$ 1*(S.S.R.)	L1	C-PVC \$ FKM
M9.00.05	12 - 24 VCC	2 wire	Flow (Frequency)	1*(4-20mA) \$ 1*(S.S.R.)	L0	PVDF \$ EPDM
M9.00.06	12 - 24 VCC	2 wire	Flow (Frequency)	1*(4-20mA) \$ 1*(S.S.R.)	L0	PVDF \$ FKM
M9.00.07	12 - 24 VCC	2 wire	Flow (Frequency)	1*(4-20mA) \$ 1*(S.S.R.)	L1	PVDF \$ EPDM
M9.00.08	12 - 24 VCC	2 wire	Flow (Frequency)	1*(4-20mA) \$ 1*(S.S.R.)	L1	PVDF \$ FKM
M9.00.09	12 - 24 VCC	2 wire	Flow (Frequency)	1*(4-20mA) \$ 1*(S.S.R.)	L0	316L SS \$ EPDM
M9.00.10	12 - 24 VCC	2 wire	Flow (Frequency)	1*(4-20mA) \$ 1*(S.S.R.)	L0	316L SS \$ FKM
M9.00.11	12 - 24 VCC	2 wire	Flow (Frequency)	1*(4-20mA) \$ 1*(S.S.R.)	L1	316L SS \$ EPDM
M9.00.12	12 - 24 VCC	2 wire	Flow (Frequency)	1*(4-20mA) \$ 1*(S.S.R.)	L1	316L SS \$ FKM



M9.00.XX

APPLICATIONS:

- Water treatment systems
- Industrial waste water treatment and recovery
- Water distribution
- Filtration systems
- Swimming pools & SPA
- Irrigation & Fertigation
- Leak detection

MAIN FEATURES:

- Wide display
- Bright backlight
- Installation flexibility
- Solid State Relays for programmable alarms
- Multilanguage menu
- USB port for software updating