

M9.05.PX – M9.05.WX

Conductivity Monitor and Transmitter



Reference	Mounting	Power supply	Wire power Technology	Sensor Input	Output	Weight (gr.)
M9.05.P1	Panel	12 - 24 VCC	3/4 wire	Conductivity	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	550
M9.05.W1	Wall	12 - 24 VCC	3/4 wire	Conductivity	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	650
M9.05.W2	Wall	110 - 230 VCA	3/4 wire	Conductivity	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	750



M9.05.PX – M9.05.WX

APPLICATIONS:

- Water treatment and regeneration
- Industrial waste water treatment and recovery
- Softener process
- Filtration systems
- Desalination process
- Demineralized water production
- Reverse osmosis/EDI process
- Cooling water monitoring
- Processing and manufacturing industry
- Chemical production

MAIN FEATURES:

- Wide full graphic display
- Multicolor backlight visualization
- Help on board
- UPW temperature compensation
- Cell constant settable freely
- Values in conductivity, resistivity, TDS
- Analog output for temperature remoting
- Mechanical relay for external device control
- Solid State Relays for programmable alarms
- USB port for software upgrading