

# M9.06.PX – M9.06.WX

pH/ORP Monitor and Transmitter



Reference	Mounting	Power supply	Wire power Technology	Sensor Input	Output	Weight (gr.)
M9.06.P1	Panel	12 - 24 VCC	3/4 wire	pH/ORP	2*(4-20mA) \$2*(S.S.R.) \$ 2* (mech. relay)	550
M9.06.W1	Wall	12 - 24 VCC	3/4 wire	pH/ORP	2*(4-20mA) \$2*(S.S.R.) \$ 2* (mech. relay)	650
M9.06.W2	Wall	110 - 230 VCA	3/4 wire	pH/ORP	2*(4-20mA) \$2*(S.S.R.) \$ 2* (mech. relay)	750



## M9.06.PX – M9.06.WX

### APPLICATIONS:

- Water treatment and regeneration
- Industrial waste water treatment and recovery
- Scrubber control
- Neutralization systems
- Heavy metals recovery
- Metal surface coating
- Processing and manufacturing industry
- Chemical production
- Swimming pools and SPA

### MAIN FEATURES

- Wide full graphic display
- Multicolor backlight visualization
- Help on board
- Automatic recognition of pH buffers
- In line adjustment
- Analog output for temperature remoting
- Mechanical relay for external device control
- Solid State Relays for programmable alarms
- USB port for software upgrading