

M9.03.PX – M9.03.WX

Dual Flow Monitor and Transmitter



Reference	Mounting	Power supply	Wire power Technology	Sensor Input	Output	Weight (gr.)
M9.03.P1	Panel	12 - 24 VCC	3/4 wire	2* Flow (Frequency)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	550
M9.03.W1	Wall	12 - 24 VCC	3/4 wire	2* Flow (Frequency)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	650
M9.03.W2	Wall	110 - 230 VCA	3/4 wire	2* Flow (Frequency)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	750



M9.03.PX – M9.03.WX

APPLICATIONS:

- Water treatment systems
- Industrial waste water treatment and recovery
- Water distribution
- Filtration systems
- Swimming pools & SPA
- Irrigation & Fertigation
- Leak detection
- Cooling water monitoring
- Processing and manufacturing industry
- Chemical production

MAIN FEATURES:

- Wide full graphic display
- Multicolor backlight
- Help on board
- Delta flow rates visualization
- Fast, intuitive and mistake-proof calibration software
- Mechanical relays for external device control
- Solid State Relays for programmable alarms
- Multilanguage menu
- USB port for software upgrading