

# M9.07.PX – M9.07.WX

Conductivity and Flow Monitor and Transmitter



Reference	Mounting	Power supply	Wire power Technology	Sensor Input	Output	Weight (gr.)
M9.07.P1	Panel	12 – 24 VCC	3/4 wire	Conductivity \$ temperature \$ Flow (Frequency)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	550
M9.07.W1	Wall	12 – 24 VCC	3/4 wire	Conductivity \$ temperature \$ Flow (Frequency)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	650
M9.07.W2	Wall	110 – 230 VCA	3/4 wire	Conductivity \$ temperature \$ Flow (Frequency)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	750

## M9.07.PX – M9.07.WX

### APPLICATIONS:

- Water treatment and regeneration
- Industrial waste water treatment and recovery
- Softener process
- Filtration systems
- Desalination process
- Demineralized water production
- Reverse osmosis process
- Cooling water monitoring
- Processing and manufacturing industry
- Chemical production

### MAIN FEATURES:

- Wide full graphic display
- Multicolor backlight
- Help on board
- Simultaneous measurement of conductivity, temperature and flow
- Fast, intuitive and mistake-proof calibration software
- Mechanical relay for external device control
- Solid State Relays for programmable alarms
- Multilanguage menus
- USB port for software upgrading