

M9.08.PX – M9.08.WX

pH/ORP & Flow Monitor and Transmitter



Reference	Mounting	Power supply	Wire power Technology	Sensor Input	Output	Weight (gr.)
M9.08.P1	Panel	12 - 24 VCC	3/4 wire	pH/ORP \$ temperature \$ Flow (Frequency)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	550
M9.08.W1	Wall	12 - 24 VCC	3/4 wire	pH/ORP \$ temperature \$ Flow (Frequency)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	650
M9.08.W2	Wall	110 - 230 VCA	3/4 wire	pH/ORP \$ temperature \$ Flow (Frequency)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	750



M9.08.PX – M9.08.WX

APPLICATIONS:

- Water treatment and regeneration
- Industrial waste water treatment and recovery
- Scrubber control
- Neutralization systems
- Heavy metals recovery
- Metal surface coating
- Processing and manufacturing industry
- Chemical production
- Swimming pools and SPA

MAIN FEATURES:

- Wide graphic display
- Multicolor backlight visualization
- Help on board
- Simultaneous measurement of pH/ORP and flow
- Intuitive calibration procedures
- Mechanical relay for external device control
- Solid State Relays for programmable alarms
- Multilanguages menu
- USB port for software upgrading