

M9.02.PX – M9.02.WX

Flow Monitor and Transmitter



Reference	Mounting	Power supply	Wire power Technology	Sensor Input	Output	Weight (gr.)
M9.02.P1	Panel	12 – 24 VCC	3/4 wire	Flow (Frequency)	1* (4-20 mA), 2* (S.S.R.), 1* (mech. relay)	500
M9.02.W1	Wall	12 – 24 VCC	3/4 wire	Flow (Frequency)	1* (4-20 mA) \$ 2* (S.S.R.) \$ 1* (mech. relay)	550
M9.02.W2	Wall	110 – 230 VCA	3/4 wire	Flow (Frequency)	1* (4-20 mA) \$ 2* (S.S.R.) \$ 1* (mech. relay)	650



M9.02.PX – M9.02.WX

APPLICATIONS:

- Water treatment systems
- Industrial waste water treatment and recovery
- Water distribution
- Filtration systems
- Swimming pools & SPA
- Irrigation & Fertigation
- Leak detection
- Cooling water monitoring
- Processing and manufacturing industry
- Chemical production

MAIN FEATURES:

- Wide full graphic display
- Multicolor backlight
- Help on board
- Installation flexibility
- Fast, intuitive and mistake-proof calibration software
- Mechanical relay for external device control
- Solid State Relays for programmable alarms
- Multilanguage menu
- USB port for software upgrading