

Data specific for pH-ORP.200

Bulb ORP Electrodes with epoxy body



Reference	Corpo	Materiale/tipo di giunzione	Soluzione di riferimento	Superficie di rilevamento	O-ring	Collegamento	Max pressione di esercizio a temperatura d'esercizio
ORP200C	resina epossidica	nylon/S.J.	KCl 3,5 M	platino	-	5 m (16,5 piedi)	7 bar a 25 °C / \$1 bar a 65 °C \$(100 psi a 77 °F/ 14,5 psi a 149 °F)
ORP222CD	resina epossidica	nylon/D.J.	KCl 3,5 M / KNO ₃ sat.	platino	silicone	Twist-Lock (BNC)	7 bar a 25 °C / \$1 bar a 65 °C \$(100 psi a 77 °F/ 14,5 psi a 149 °F)
ORP223CD	resina epossidica	nylon/D.J.	KCl 3,5 M / KNO ₃ sat.	platino	silicone	Twist-Lock (BNC)	7 bar a 25 °C / \$1 bar a 65 °C \$(100 psi a 77 °F/ 14,5 psi a 149 °F)
PH200C	resina epossidica	nylon/S.J.	KCl 3,5 M	membrana in vetro di pH	-	5 m (16,5 piedi)	7 bar a 25 °C / \$1 bar a 65 °C \$(100 psi a 77 °F/ 14,5 psi a 149 °F)
PH222CD	resina epossidica	nylon/D.J.	KCl 3,5 M / KNO ₃ sat.	membrana in vetro di pH	silicone	Twist-Lock (BNC)	7 bar a 25 °C / \$1 bar a 65 °C \$(100 psi a 77 °F/ 14,5 psi a 149 °F)
PH222CDTC	resina epossidica	nylon/D.J.	KCl 3,5 M / KNO ₃ sat.	membrana in vetro di pH	-	5 m (16,5 piedi)	7 bar a 25 °C / \$1 bar a 65 °C \$(100 psi a 77 °F/ 14,5 psi a 149 °F)
PH223CD	resina epossidica	nylon/D.J.	KCl 3,5 M / KNO ₃ sat.	membrana in vetro di pH	silicone	Twist-Lock (BNC)	7 bar a 25 °C / \$1 bar a 65 °C \$(100 psi a 77 °F/ 14,5 psi a 149 °F)

Data specific for pH-ORP.200

APPLICATIONS:

- Water treatment
- Neutralization systems
- Water quality monitoring
- Swimming Pools and spas
- Aquaculture
- Agriculture and fertilizing systems
- Process control

MAIN FEATURES:

- Epoxy body
- Single or double junction technology
- Large gel reference volume
- Easy and quick installation system
- Outline cable or BNC connection
- Version with temperature sensor combined
- Special versions on request
- Low cost fittings