

PH2XX

Bulb pH Electrodes with epoxy body



Reference	Features	Operative Range	Cable***	Connection	Installation	Weight (gr.)
PH200C	Singol junction	0-14 pH**	Not required	5m \$ (16,5 ft.) Cable	EG50P \$ EG75P \$ MK150200 \$ MIFV20X05 \$ MIMC20X05	200
PH222CD	Double junction	0-14 pH**	CN 653 \$ CN 653 TC1	Twist-lock (BNC)	EG50P \$ EG75P \$ MIFV20X05 \$ MIMC20X05	90
PH222CDTC	Double junction with Pt100 included	0-14 pH**	Not required	5m \$ (16,5 ft.) Cable	EG50P \$ EG75P \$ MK150200 \$ MIFV20X05 \$ MIMC20X05	220
PH223CD	Double junction for FLS fittings	0-14 pH**	CN 653	Twist-lock (BNC)	F3.SP2.4	100

PH2XX

APPLICATIONS:

- Water treatment
- Neutralization systems
- Water quality monitoring
- Swimming Pools and spas
- Aquaculture
- Agriculture and fertilizing systems
- Process control

MAIN FEATURES:

- Epoxy body
- Single or double junction technology
- Large gel reference volume
- Easy and quick installation system
- Outline cable or BNC connection
- Version with temperature sensor combined
- Special versions on request
- Low cost fittings