

# ORP2XX

Bulb ORP Electrodes with epoxy body



| Reference | Features                         | Operative Range | Cable**      | Connection             | Installation   | Weight (gr.) |
|-----------|----------------------------------|-----------------|--------------|------------------------|--|--------------|
| ORP200C   | Singol junction                  | ± 2000 mV       | Not required | 5m \$ (16,5 ft.) Cable | EG50P \$ EG75P \$ MK150200 \$ MIFV20X05 \$ MIMC20X05 | 200          |
| ORP222CD  | Double junction                  | ± 2000 mV       | CN 653       | Twist-lock (BNC)       | EG50P \$ EG75P \$ MIFV20X05 \$ MIMC20X05             | 90           |
| ORP223CD  | Double junction for FLS fittings | ± 2000 mV       | CN 653       | Twist-lock (BNC)       | F3.SP2.4   | 100          |

# ORP2XX

## APPLICATIONS:

- Water treatment
- Neutralization systems
- Water quality monitoring
- Swimming Pools and spas
- Aquaculture
- Agriculture and fertilizing systems
- Process control

## MAIN FEATURES:

- Epoxy body
- Single or double junction technology
- Large gel reference volume
- Easy and quick installation system
- Outline cable or BNC connection
- Version with temperature sensor combined
- Special versions on request
- Low cost fittings